



ALVI Officine Meccaniche E. Viazzo & C. s.r.l.

S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA Tel. +39 0161 234600 - Fax +39 0161 234633 E-mail: info@alvi-italia.com - www.alvi-italia.com

2050/162 CR

RD20500N162

Container with lid, tight separation, front doors and rubber bumper

Body in AIMg3 light alloy sheet, anodized (10 micron). Smooth not perforated walls, upper rim dia. 20 mm with inner strengthening. Front door divided in three parts: the lower part fixed, the central one sliding and the upper one tipping-over and fixed by hinges. Lid divided in two parts: 1/3 fixed 2/3 in open position up to 130° with nylon and stainless steel hinges. One push-handle on a short side. Tight separation wall and silicon seal on bottom, 2 Drain taps. Strong non-twisting bottom iron frame with epoxy finishing (80 micron). Non-marking grey rubber buffer on bottom. 2 fixed and 2 swivelling wheels dia. 160 mm with non-marking rubber ring and zinc-plated housings.



Internal dimensions | 1000 x 600 x 1165 mm h

External dimensions

1100 x 650 x 1425 mm h

Capacity 714

Weight | 37,50 kg

Wheels diameter | 160 mm

Wheels position |2 + 2|