



ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: info@alvi-italia.com - www.alvi-italia.com

3162 CR

RH3162ON001

Cupboard trolley with 3 sections and capacity 8 STU

Body in AlMg3 light alloy sheet, anodized (10 micron). Internal frame with 2 sections made in anodized light alloy profiles and nylon fiberglass rails with stopping system, useful width 302 mm suitable to be equipped with metal containers placed on shelves BLSFL3004 or polypropylene containers with lids (BGDNN...) without shelves. Double wing door built with 2,5 mm bent sheet, with continuous hinges, opening at 270° with additional stopping position at 260° for disinfection inside tunnels. Door fastening by one vertical thumb-latch hooking on top and bottom. The truck is equipped with an EPDM gasket all around the opening: door, bottom and cover. The gasket, the central junction and the four corners of the opening grant airtight protection during the transport outside sterile areas. One push-handle on each short side. Light alloy strong non-twisting bottom frame. Non-marking grey rubber buffer on bottom and on top. 2 fixed and 2 swivelling wheels dia. 160 mm with super elastic grey rubber ring, balls-bearings with waterproof plastic protection and stainless steel housings. Rails carrying capacity: 20 kg Maximum capacity 8 sterile units 300x600x300 mm h or 8 polypropylene containers 530x325x200 mm h.



Internal dimensions	877 x 630 x 1220 mm h
External dimensions	977 x 710 x 1585 mm h
Capacity	8 STU 300 mm h or 8 BGDNN70200B
Weight	71 kg
Wheels diameter	160 mm