



ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: info@alvi-italia.com - www.alvi-italia.com

86265, 8622 CR

RH8625XN001

Cupboard truck in stainless steel with 2 height adjustable shelves

Body in AISI 304 stainless steel sheet with water tight TIG welding on top and bottom. Smooth walls without cutting edges or interstices. Internal frame with 2 height adjustable shelves. Double walled doors with opening and locking in open position at 270 °. Push closing device with hook on top and bottom. Push closing device with hook on top and bottom. The truck is equipped with a silicone gasket all around the opening: door, bottom and lid. 2 vertical push-handles on each short side. Strong non-twisting bottom frame in AISI 304 stainless steel. PE buffer on bottom. 2 fixed and 2 swivelling wheels dia. 160 mm with super elastic grey rubber ring, and zinc plated housings. 2 independent brakes. In case of use of washing tunnels it is necessary to add the option: wheels with stainless steel housings.



Internal dimensions	1010 x 630 x 1200 mm h
External dimensions	1235 x 711 x 1507 mm h
Capacity	9 STU 300 mm h
Wheels diameter	160 mm
Material	AISI 304 stainless steel



ALVI Officine Meccaniche E. Viazzo & C. s.r.l.

S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA

Tel. +39 0161 234600 - Fax +39 0161 234633

E-mail: info@alvi-italia.com - www.alvi-italia.com

86265, 8622 CR

RH8622XN001

Cupboard truck in stainless steel with 2 height adjustable shelves

Body in AISI 304 stainless steel sheet with water tight TIG welding on top and bottom. Smooth walls without cutting edges or interstices. Internal frame with 2 height adjustable shelves. Double walled doors with opening and locking in open position at 270 °. Push closing device with hook on top and bottom. Push closing device with hook on top and bottom. The truck is equipped with a silicone gasket all around the opening: door, bottom and lid. 2 vertical push-handles on each short side. Strong non-twisting bottom frame in AISI 304 stainless steel. PE buffer on bottom. 2 fixed and 2 swivelling wheels dia. 160 mm with super elastic grey rubber ring, and zinc plated housings. 2 independent brakes. In case of use of washing tunnels it is necessary to add the option: wheels with stainless steel housings.



Internal dimensions 800 x 630 x 1200 mm h

External dimensions 1025 x 711 x 1507 mm h

Capacity 6 STU 300 mm h

Wheels diameter 160 mm

Material AISI 304 stainless steel