ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: info@alvi-italia.com - www.alvi-italia.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001:2015 =

BA 20 2+2

RABA20ON001

Anodized light alloy trolley with 2+2 wheels

Body in AlMg3 light alloy sheet, anodized (10 micron). Ribbed not perforated walls, uppper rim dia. 20 mm with inner strengthening. Bottom light alloy frame. All around light alloy buffer. 2 fixed and 2 swivelling wheels with non-marking rubber ring and zinc-plated housings.

Internal dimensions	1000 x 500 x 610 mm h
External dimensions	1030 x 530 x 770 mm h
Capacity	305 l
Weight	16,70 kg
Wheels diameter	100 mm
Wheels position	2+2

ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: info@alvi-italia.com - www.alvi-italia.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001:2015 =

BA 20 2+2

RABA20ON003

Anodized light alloy trolley with 2+2 wheels

Body in AlMg3 light alloy sheet, anodized (10 micron). Ribbed not perforated walls, uppper rim dia. 20 mm with inner strengthening. Bottom light alloy frame. All around light alloy buffer. 2 fixed and 2 swivelling wheels with non-marking rubber ring and zinc-plated housings.

Internal dimensions	1000 x 600 x 610 mm h
External dimensions	1030 x 630 x 770 mm h
Capacity	366 l
Weight	17,80 kg
Wheels diameter	100 mm
Wheels position	2+2

ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: info@alvi-italia.com - www.alvi-italia.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001:2015 =

BA 20 2+2

RABA20ON009

Anodized light alloy trolley with 2+2 wheels

Body in AlMg3 light alloy sheet, anodized (10 micron). Ribbed not perforated walls, uppper rim dia. 20 mm with inner strengthening. Bottom light alloy frame. All around light alloy buffer. 2 fixed and 2 swivelling wheels with non-marking rubber ring and zinc-plated housings.

Internal dimensions	920 x 680 x 685 mm h
External dimensions	950 x 710 x 875 mm h
Capacity	428 l
Weight	20,40 kg
Wheels diameter	125 mm
Wheels position	2+2

ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: info@alvi-italia.com - www.alvi-italia.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001:2015 =

BA 20 2+2

RABA20ON005

Anodized light alloy trolley with 2+2 wheels

Body in AlMg3 light alloy sheet, anodized (10 micron). Ribbed not perforated walls, uppper rim dia. 20 mm with inner strengthening. Bottom light alloy frame. All around light alloy buffer. 2 fixed and 2 swivelling wheels with non-marking rubber ring and zinc-plated housings.

Internal dimensions	1300 x 700 x 610 mm h
External dimensions	1330 x 730 x 805 mm h
Capacity	555 l
Weight	25 kg
Wheels diameter	125 mm
Wheels position	2+2

ALVI Officine Meccaniche E. Viazzo & C. s.r.l.
S.S. 230 n. 49 - 13030 CARESANABLOT (VC) - ITALIA
Tel. +39 0161 234600 - Fax +39 0161 234633
E-mail: info@alvi-italia.com - www.alvi-italia.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001:2015 =

BA 20 2+2

RABA20ON007

Anodized light alloy trolley with 2+2 wheels

Body in AlMg3 light alloy sheet, anodized (10 micron). Ribbed not perforated walls, uppper rim dia. 20 mm with inner strengthening. Bottom light alloy frame. All around light alloy buffer. 2 fixed and 2 swivelling wheels with non-marking rubber ring and zinc-plated housings.

Internal dimensions	1300 x 700 x 685 mm h
External dimensions	1330 x 730 x 880 mm h
Capacity	623 l
Weight	27 kg
Wheels diameter	125 mm
Wheels position	2+2